


6242Y

PVC Flat Wiring Cable with Bare CPC. BS 6004. 300/500 V



Draka 6242Y is a flat PVC insulated and sheathed low voltage wiring cable typically used for small power and lighting applications

Two core with bare CPC

KEY APPLICATIONS

Suitable for fixed installation in industrial, commercial and domestic premises, installation in walls, on boards, in conduit, trunking or embedded in plaster for small power and lighting applications

FEATURES AND BENEFITS

- Ideal for ring and radial circuits
- Ideal for lighting and switching circuits
- Easy to strip
- Manufactured under ISO 9001 Quality management systems

STANDARDS



BS 6004
BS EN 60332-1-2

Construction Standard
Flame Propagation - Single Cable

CONSTRUCTION

Conductor material	Copper
Conductor surface	Bare
Core insulation material	Polyvinyl chloride (PVC)
Material outer sheath	Polyvinyl chloride (PVC)
Cable shape	Flat

APPLICATIONS PROPERTIES

Nominal voltage U ₀ [V]	300
Nominal voltage U [V]	500
Flame retardant	In accordance with BS EN 60332-1-2
Max. conductor temperature [°C]	70
Min. Operation temperature [°C]	-15
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	60
Bending radius (rule)	4D (Minor axis)

COLOURS

Insulation: Brown, Blue
Alternatively, Brown, Brown (for 2x1.0 and 2x1.5 only)
Sheath: Grey

CURRENT RATINGS

Refer to table 4D5 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

TECHNICAL DATA

Number of cores	Nominal cross section conductor [mm ²]	Conductor category	Nominal cross section of protective conductor [mm ²]	Cable height approx. [mm]	Cable width approx. [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
2	1	Class 1 = solid	1	4.5	8.2	58	18.1
2	1.5	Class 1 = solid	1	4.7	8.6	74	12.1
2	2.5	Class 1 = solid	1.5	5.3	9.9	110	7.41
2	4	Class 2 = stranded	1.5	6.1	11.4	155	4.61
2	6	Class 2 = stranded	2.5	6.8	13.1	215	3.08
2	10	Class 2 = stranded	4	8.4	16.8	350	1.83
2	16	Class 2 = stranded	6	9.6	19.5	520	1.15