

## BS 5467 1kV

PVC Copper Conductor Armoured Cable. BS 5467. 600/1000 V



Draka BS 5467 is a low voltage armoured cable for industrial wiring and mains distribution

### KEY APPLICATIONS

Designed primarily for clipped directly to a surface, on tray, in basket or in free air. These cables can also be laid direct in ground or in ducts in free draining soil, or embedded in concrete

The design of Draka BS 5467 is particularly robust and is well suited to areas at risk of mechanical damage.

### FEATURES AND BENEFITS

- Manufactured under ISO 9001 Quality management systems
- Single core aluminium wire armour
- Multi core steel wire armour

### STANDARDS



**BS 5467**

**BS EN 60332-1-2**

Construction Standard

Flame Propagation - Single Cable

CONSTRUCTION

Conductor material	Copper
Conductor surface	Bare
Core insulation material	XLPE
Armouring/reinforcement	Wire
Armouring	Yes
Material inner sheath	Polyvinyl chloride (PVC)
Material outer sheath	Polyvinyl chloride (PVC)
Cable shape	Round

APPLICATIONS PROPERTIES

Nominal voltage U0 [V]	600
Nominal voltage U [V]	1,000
Flame retardant	In accordance with BS EN 60332-1-2
Max. conductor temperature [°C]	90
Min. Operation temperature [°C]	-15
UV resistant	Yes
Outdoor installation	Yes
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	80
Underground installation	Yes
Bending radius (rule)	8D

COLOURS

Insulation: Single Core: Brown or Blue;  
Two Cores: Brown, Blue;  
Three Cores: Brown, Black, Grey;  
our Cores: Blue, Brown, Black, Grey;  
Five Cores: Blue, Brown, Black, Grey, Green/Yellow;  
7 to 37 Cores: White (with printed numbers);  
Sheath: Black

CURRENT RATINGS

Refer to table 4E3 and 4E4 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations  
Note: Where a conductor operates at a temperature exceeding 70°C it shall be ascertained that the equipment connected to the conductor is suitable for the conductor operating temperature

## TECHNICAL DATA

Number of cores	Nominal cross section conductor [mm <sup>2</sup> ]	Shape of conductor	Nominal diameter of armouring wire [mm]	Nominal diameter under armour [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
1	150	Round	1.6	23	27	1,850	0.124
1	185	Round	1.6	25	29	2,300	0.0991
1	240	Round	1.6	27	31	2,900	0.0754
1	300	Round	1.6	30	34	3,500	0.0601
1	400	Round	2	35	39	4,500	0.047
1	500	Round	2	38	43	5,600	0.0366
1	630	Round	2	42	46	7,000	0.0283
1	800	Round	2.5	49	54	9,000	0.0221
1	1,000	Round	2.5	54	59	11,400	0.0176
2	1.5	Round	0.9	8.7	11.3	260	12.1
2	2.5	Round	0.9	9.9	12.7	330	7.41
2	4	Round	0.9	11	13.8	390	4.61
2	6	Round	0.9	12.1	14.9	470	3.08
2	10	Round	0.9	13.7	16.7	610	1.83
2	16	Round	0.9	16.5	19.5	920	1.15
2	25	Sector-shaped	1.25	18.2	22	1,100	0.727
2	35	Sector-shaped	1.25	21	24	1,500	0.524
2	50	Sector-shaped	1.6	24	27	1,850	0.387
2	70	Sector-shaped	1.6	26	30	2,400	0.268
2	95	Sector-shaped	1.6	28	32	3,100	0.193
2	120	Sector-shaped	2	31	36	3,800	0.153
2	150	Sector-shaped	2	34	38	4,400	0.124
2	185	Sector-shaped	2	38	43	5,800	0.0991
2	240	Sector-shaped	2.5	43	48	7,100	0.0754
2	300	Sector-shaped	2.5	47	53	8,600	0.0601
2	400	Sector-shaped	2.5	52	58	10,500	0.047
3	1.5	Round	0.9	9.1	11.7	285	12.1
3	2.5	Round	0.9	10.4	13.2	360	7.41
3	4	Round	0.9	11.6	14.4	440	4.61
3	6	Round	0.9	12.8	15.6	540	3.08
3	10	Round	1.25	15.2	18.2	820	1.83
3	16	Round	1.25	17.4	21	1,100	1.15
3	25	Round	1.6	23	26	1,700	0.727
3	35	Round	1.6	25	29	2,100	0.524
3	50	Sector-shaped	1.6	27	30	2,500	0.387

TECHNICAL DATA

Number of cores	Nominal cross section conductor [mm²]	Shape of conductor	Nominal diameter of armouring wire [mm]	Nominal diameter under armour [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
3	70	Sector-shaped	1.6	29	33	3,100	0.268
3	95	Sector-shaped	2	33	37	4,200	0.193
3	120	Sector-shaped	2	36	40	5,100	0.153
3	150	Sector-shaped	2.5	41	45	6,400	0.124
3	185	Sector-shaped	2.5	44	49	7,700	0.0991
3	240	Sector-shaped	2.5	49	54	9,700	0.0754
3	300	Sector-shaped	2.5	54	59	11,700	0.0601
3	400	Sector-shaped	2.5	60	65	14,500	0.047
4	1.5	Round	0.9	9.8	12.4	315	12.1
4	2.5	Round	0.9	11.3	13.9	405	7.41
4	4	Round	0.9	12.6	15.4	510	4.61
4	6	Round	1.25	14.7	17.5	730	3.08
4	10	Round	1.25	16.5	19.5	960	1.83
4	16	Round	1.25	19.1	23	1,300	1.15
4	25	Round	1.6	25	28	2,100	0.727
4	35	Round	1.6	27	31	2,600	0.524
4	50	Sector-shaped	1.6	30	34	3,100	0.387
4	70	Sector-shaped	2	33	37	4,000	0.268
4	95	Sector-shaped	2	36	41	5,100	0.193
4	120	Sector-shaped	2.5	41	46	6,600	0.153
4	150	Sector-shaped	2.5	45	50	7,900	0.124
4	185	Sector-shaped	2.5	50	55	9,600	0.0991
4	240	Sector-shaped	2.5	55	61	12,200	0.0754
4	300	Sector-shaped	2.5	61	66	14,800	0.0601
4	400	Sector-shaped	3.15	69	75	19,200	0.047
5	1.5	Round	0.9	11.8	14.6	410	12.1
5	2.5	Round	0.9	13.3	16.1	500	7.41
5	4	Round	0.9	14.8	17.8	630	4.61
5	6	Round	1.25	17.2	21	900	3.08
5	10	Round	1.25	20	24	1,250	1.83
5	16	Round	1.6	23	27	1,700	1.15
5	25	Round	1.6	28	31	2,500	0.727
5	35	Round	1.6	30	34	2,900	0.524
7	1.5	Round	0.9	12.8	15.4	475	12.1
7	2.5	Round	0.9	14.6	17.2	610	7.41

Copyright Prysmian - 2024 You may not copy, reprint or reproduce in any form the content, either wholly or in part, of this Datasheet, without the written permission of the copyright owner. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian; any modification or alteration afterwards of product may give different result. The information is believed to be correct at the time of issue. Prysmian reserves the right to amend the information within this Datasheet without prior notice. This Datasheet may include inaccuracies, omissions of content and of information and is not contractually valid unless specifically authorised by Prysmian. Draka U.K. Limited acts as agent for and on behalf of Prysmian Cables & Systems Limited. Property of Prysmian Group UK - Uncontrolled when printed Draka UK Limited  
Chickenhall Lane, Eastleigh, Hampshire, SO50 6YU, United Kingdom

TECHNICAL DATA

Number of cores	Nominal cross section conductor [mm²]	Shape of conductor	Nominal diameter of armouring wire [mm]	Nominal diameter under armour [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
7	4	Round	1.25	16.1	18.9	830	4.61
12	1.5	Round	1.25	16.5	19.5	760	12.1
12	2.5	Round	1.25	18.9	23	980	7.41
12	4	Round	1.6	22	25	1,400	4.61
19	1.5	Round	1.25	18.7	22	960	12.1
19	2.5	Round	1.6	23	26	1,450	7.41
19	4	Round	1.6	25	29	1,850	4.61
27	1.5	Round	1.6	23	27	1,400	12.1
27	2.5	Round	1.6	27	31	1,850	7.41
27	4	Round	1.6	30	34	2,400	4.61
37	1.5	Round	1.6	26	29	1,700	12.1
37	2.5	Round	1.6	30	34	2,300	7.41