

## 6491B (H07Z-R)

**OHLS® Single Core Conduit Wire. BS EN 50525-3-41. 450/750 V**



Draka 6491B is a single core, low voltage Zero Halogen, Low Smoke (OHLS®) wiring cable designed for installation within conduit, trunking or inside fixed protected environments

### KEY APPLICATIONS

Installation in surface mounted or embedded conduits, or similar closed systems and for fixed protected installation in or on lighting fittings and inside appliances, switch gear and control gear particularly for situations in which low emissions of smoke and acid gas is required.

Green/Yellow for use as earth can be installed without mechanical protection.

### FEATURES AND BENEFITS

- Zero Halogen, Low Smoke (OHLS®)
- Manufactured under ISO 9001 Quality management systems

### STANDARDS



**BS EN 50525-3-41**

**BS EN 60332-1-2**

**BS EN 61034-2**

**BS EN 60754-1**

Construction Standard

Flame Propagation - Single Cable

Smoke emission

Corrosive and acid gas

### CONSTRUCTION

Conductor material

Copper

Conductor surface

Bare

Core insulation material

Low smoke zero halogen

## APPLICATIONS PROPERTIES

Nominal voltage U <sub>0</sub> [V]	450
Nominal voltage U [V]	750
Flame retardant	In accordance with BS EN 60332-1-2
Halogen free	Yes
Low smoke	Yes
Max. conductor temperature [°C]	90
Min. Operation temperature [°C]	-25
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	80
Bending radius (rule)	6D

## COLOURS

A range of insulation colours are available, including green/yellow

## CURRENT RATINGS

Refer to table 4E1 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

Note: Where a conductor operates at a temperature exceeding 70°C it shall be ascertained that the equipment connected to the conductor is suitable for the conductor operating temperature

## TECHNICAL DATA

Nominal cross section conductor [mm <sup>2</sup> ]	Conductor category	Nominal thickness insulation [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
1.5	Class 2 = stranded	0.7	3	22	12.1
2.5	Class 2 = stranded	0.8	3.7	33	7.41
4	Class 2 = stranded	0.8	4.2	48	4.61
6	Class 2 = stranded	0.8	4.8	68	3.08
10	Class 2 = stranded	1	6.3	120	1.83
16	Class 2 = stranded	1	6.9	175	1.15
25	Class 2 = stranded	1.2	8.4	260	0.727
35	Class 2 = stranded	1.2	9.5	350	0.524
50	Class 2 = stranded	1.4	11.2	475	0.387
70	Class 2 = stranded	1.4	12.8	670	0.268
95	Class 2 = stranded	1.6	15.2	940	0.193
120	Class 2 = stranded	1.6	16.5	1,200	0.153
150	Class 2 = stranded	1.8	18.4	1,450	0.124
185	Class 2 = stranded	2	21	1,800	0.0991
240	Class 2 = stranded	2.2	24	2,400	0.0754
300	Class 2 = stranded	2.4	26	3,000	0.0601
400	Class 2 = stranded	2.6	30	3,800	0.047
500	Class 2 = stranded	2.8	34	4,900	0.0366
630	Class 2 = stranded	2.8	37	6,100	0.0283