

6181Y

PVC Insulated and Sheathed Single Core Cable. BS 6004. 300/500 V



Draka 6181Y is a low voltage single core, PVC insulated copper conductor with an additional PVC oversheath insulation for physical protection

KEY APPLICATIONS

Fixed installation in dry or damp premises on walls, boards or trays, in channels or embedded in plaster

FEATURES AND BENEFITS

• Manufactured under ISO 9001 Quality management systems

STANDARDS



BS 6004 BS EN 60332-1-2 Construction Standard

Flame Propagation - Single Cable

CONSTRUCTION

Conductor material Conductor surface Core insulation material Material outer sheath Cable shape Copper Bare

Polyvinyl chloride (PVC) Polyvinyl chloride (PVC)

Round

GB40_6181Y_20251104 P1



APPLICATIONS PROPERTIES

Nominal voltage U0 [V] 300
Nominal voltage U [V] 500

Flame retardant In accordance with BS EN 60332-1-2

Max. conductor temperature [°C]70Min. Operation temperature [°C]-15Min. Installation temperature [°C]0Max. Installation temperature [°C]60Bending radius (rule)4D

COLOURS

Insulation: Brown or Blue.

Sheath: Grey

CURRENT RATINGS

Refer to table 4D1 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations



TECHNICAL DATA

Nominal cross section conductor [mm²]	Conductor category	Nominal thickness insulation [mm]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
1.5	Class 1 = solid	0.8	4.5	35	12.1
2.5	Class 1 = solid	0.8	5.1	48	7.41
4	Class 2 = stranded	0.8	6.1	71	4.61
6	Class 2 = stranded	0.8	6.6	93	3.08
10	Class 2 = stranded	1	7.8	145	1.83
16	Class 2 = stranded	1	9	210	1.15
25	Class 2 = stranded	1.2	10.9	320	0.727
35	Class 2 = stranded	1.2	12	420	0.524

Р3