

FT30SAFFIRE

Fire Resistant Cable. BS 7629-1. 300/500 V



Draka Firetuf® FT30 Saffire is a **'Standard'** fire resistant cable as defined by fire alarm and emergency lighting British Standards

KEY APPLICATIONS

- Fire detection and fire alarm systems for buildings.
- Voice alarm systems and emergency voice communication.
- Emergency and escape lighting.
- Control circuits for life safety and fire fighting systems.
- Other essential service control circuits for "**Standard**" fire resistance.

FEATURES AND BENEFITS

- Fully screened
- Full size CPC in direct contact with screen
- Tough insulation, compliant with type E15 to BS EN 50363-5
- Zero Halogen, Low Smoke (OHLS®) sheath
- Easy termination
- BS 8519 - Category 1, Code of Practice - Life Safety and Firefighting Systems
- BS 5839-1 - "**Standard**", Code of Practice - Fire Alarms
- BS 5266-1 - "**Standard**", Code of Practice - Emergency Lighting
- Manufactured under ISO 9001 Quality management systems

STANDARDS



BS 7629-1 - Standard 60 (2, 3 & 4 cores, 1.5mm² to 4mm²)
BS EN 50200 - PH30
BS EN 50200 - PH60
BS EN 50200 - ANNEX E
BS 6387 Category CWZ
BS EN 60332-1-2
BS EN 61034-2
BS EN 60754-1

Construction Standard
Fire Resistant Test - Flame & Shock - 30 Minutes
Fire Resistant Test - Flame & Shock - 60 Minutes
Fire Resistant Test - Flame, Shock & Water - 30 Minutes
Fire Resistant Tests
Flame Propagation - Single Cable
Smoke emission
Corrosive and acid gas

CONSTRUCTION

Conductor material	Copper
Conductor surface	Bare
Core insulation material	Low smoke zero halogen
Screen construction	Metallised foil
Screen	Yes
Screen material	Aluminium
Material outer sheath	Low smoke zero halogen
Cable shape	Round

APPLICATIONS PROPERTIES

Nominal voltage U ₀ [V]	300
Nominal voltage U [V]	500
Flame retardant	In accordance with BS EN 60332-1-2
Halogen free	Yes
Low smoke	Yes
Max. conductor temperature [°C]	70
Min. Operation temperature [°C]	-25
UV resistant	Yes
Outdoor installation	Yes
Min. Installation temperature [°C]	0
Max. Installation temperature [°C]	60
Bending radius (rule)	6D

COLOURS

Insulation: Two Cores: Brown, Blue;
Three Cores: Brown, Black, Grey;
Four Cores: Blue, Brown, Black, Grey
Sheath: Red or White

CURRENT RATINGS

Refer to table 4D2 of BS 7671 Requirements for Electrical Installations. IET Wiring Regulations

TECHNICAL DATA

Number of cores	Nominal cross section conductor [mm ²]	Conductor category	Nominal cross section of protective conductor [mm ²]	Nominal outer diameter [mm]	Cable weight [kg/km]	Conductor resistance at 20° C [Ohm/km]
2	1.5	Class 1 = solid	1.5	7.9	91	12.1
2	1.5	Class 2 = stranded	1.5	8.2	97	12.1
2	2.5	Class 1 = solid	2.5	9.5	140	7.41
2	2.5	Class 2 = stranded	2.5	9.5	145	7.41
2	4	Class 2 = stranded	4	11.6	205	4.61
3	1.5	Class 1 = solid	1.5	8.5	120	12.1
3	2.5	Class 1 = solid	2.5	10.4	180	7.41
3	4	Class 2 = stranded	4	12.3	260	4.61
4	1.5	Class 1 = solid	1.5	10	150	12.1
4	2.5	Class 1 = solid	2.5	11.9	225	7.41
4	4	Class 2 = stranded	4	13.5	320	4.61
7	1.5	Class 2 = stranded	1.5	13.5	250	12.1